

Q8 Mozart CL 20 SAE 50

High performance cylinder oil for two stroke crosshead engines

Description

Q8 Mozart CL is a high performance cylinder oil for two stroke crosshead engines operating at high pressure and high temperature conditions. TBN 20 is recommended for low sulphur fuels.

Applications

For lubricating the cylinders of all large slow-speed marine diesel engines.

Features

Enhanced technology

Benefits

Excellent quality base oils, maintaining a strong oil film under all load conditions

Excellent protection against rust and corrosion, protecting all metal surfaces even under extreme conditions

Properties

| | Method | Unit | Typical |
|-----------------------------|--------|--------------------|---------|
| Viscosity Grade | - | - | SAE 50 |
| Density, 15 °C | D 4052 | g/ml | 0.930 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 196 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 17.8 |
| Viscosity Index | D 2270 | - | 100 |
| Flash Point, P-M | D 93 | °C | 196 |
| Pour Point | D 97 | °C | -12 |
| Total Base Number | D 2896 | mg KOH/g | 20 |

The figures above are not a specification. They are typical figures obtained within production tolerances.