

Q8 T 1000 15W-40

Advanced Super Tractor Universal Oil (STOU)

Description

Q8 T 1000 15W-40 is a super tractor universal oil that guarantees an excellent performance for your equipment. This versatile single solution oil is used as a lubrication of diesel and gasoline engines, transmissions and final drives and as a brake, clutch and hydraulic fluid. Q8 T 1000 15W-40 meets the requirements of API and ACEA and several OEMs.

Applications

Q8 T 1000 15W-40 is used as a single lubricant for a wide range of machinery, such as engines, transmissions and final drivers. It is also applied as a brake, clutch or hydraulic fluid. Q8 T 1000 15W-40 is recommended for diesel and gasoline engines. It meets the requirements of API and ACEA and OEMs John Deere, Mercedes-Benz and ZF.

Benefits

- Excellent transmission lubrication.
- Outstanding hydraulic fluid properties.
- Limits wet brake noise while limiting friction plate wear.
- Excellent response of hydraulic components.
- Excellent anti-foaming properties.

Specifications, recommendations and approvals

ACEA	E3	John Deere	JDM J27
ACEA	E7 level of soot control, wear and piston cleanliness	MB	227.1
API	CE	Massey Ferguson	CMS M 1135
API	CF	Massey Ferguson	CMS M 1139
API	CI-4 level of soot control	Massey Ferguson	CMS M 1143
API	GL-4	Massey Ferguson	CMS M 1144
Allison	C-4	Massey Ferguson	CMS M 1145
Case New Holland	MAT 3525	New Holland	NH 024-C
Case New Holland	MAT 3526	New Holland	NH 030-C
Ford	M2C134-D	New Holland	NH 410-B
Ford	M2C159-B	New Holland	NH 420-A
Ford	M2C159-C	ZF	TE-ML 06B
John Deere	JDM J20C	ZF	TE-ML 06C

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,871
Density, 15 °C	D 4052	g/ml	0,874
Viscosity Grade	-	-	SAE 15W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	118
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15,9
Viscosity Index	D 2270	-	143
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	234

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 T 1000 SAE 15W-40 has been approved by AGCO/Fendt for use in CVT ML 200 transmissions. Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 1000 15W-40 is **1.35 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**