

## Q8 T 660 5W-40

ACEA A3/B4 passenger car engine oil

### Description

High performance synthetic engine oil for passenger cars and vans with normally aspirated or turbocharged gasoline, Synthetic year round engine lubricant. It meets the requirements of ACEA A3/B4.

### Applications

High performance synthetic engine oil for passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or diesel engines and direct injection diesel engines. Specially recommended for high performance, multi-valve engines with catalyst.

### Benefits

- Outstanding friction reduction.
- Outstanding engine protection after cold starting.
- Outstanding oil film strength preventing engine wear.
- Excellent prevention of black sludge formation.

### Specifications, recommendations and approvals

<b>ACEA</b>	A3/B4	<b>Renault</b>	RN 0700
<b>API</b>	SM	<b>Renault</b>	RN 0710
<b>GM</b>	LL-B-025	<b>VAG</b>	VW 502.00
<b>MB</b>	229.3	<b>VAG</b>	VW 505.00

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,858
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	81,9
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.6
Viscosity Index	D 2270	-	169
Apparent Viscosity, -30 °C	D 5293	mPa.s	6400
Pour Point	D 97	°C	-33
Flash Point, P-M	D 93	°C	221
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.