

Q8 T 800 10W-30

Synthetic based API CI-4 and ACEA E7 heavy-duty engine oil

Description

Q8 T 800 10W-30 is a super high performance heavy-duty engine oil which offers optimum engine durability and prevents deposit formation. This lubricant provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs and prevents corrosion and foaming.

Applications

Q8 T 800 10W-30 is designed for normally aspirated, turbocharged or supercharged engines, with or without intercooling. It is recommended for most heavy-duty diesel engines for on- and off highway applications. It meets the ACEA E7 and API CI-4 specification as well as the requirements of MAN, MB, Volvo, Caterpillar, Cummins and MTU. Can also be used for Passenger Cars requiring API SL.

Benefits

- Premium protection against engine wear.
- Advanced engine protection after cold start.
- High protection against piston rings deposits.
- High protection against rust and corrosion.

Specifications, recommendations and approvals

| ACEA | E7 | Cummins | CES 20077 |
|-------------|-----------|---------|---------------------|
| API | CI-4 | Cummins | CES 20078 |
| API | SL | MAN | M 3275-1 |
| Caterpillar | ECF-1a | МВ | 228.3 (DTFR 15B110) |
| Caterpillar | ECF-2 | Mack | EO-M Plus |
| Cummins | CES 20071 | Renault | RLD |
| Cummins | CES 20072 | Renault | RLD-2 |
| Cummins | CES 20076 | Volvo | VDS-2 |
| | | | |

Properties

| | Method | Unit | Typical |
|--------------------------------|--------|----------|------------|
| Density, 15 °C | D 4052 | g/ml | 0,875 |
| Viscosity Grade | - | - | SAE 10W-30 |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 75 |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 11.3 |
| Viscosity Index | D 2270 | - | 146 |
| Total Base Number | D 2896 | mg KOH/g | 10 |
| Pour Point | D 97 | °C | -45 |
| Flash Point, COC | D 92 | °C | 220 |
| Sulfated Ash | D 874 | % mass | 1.3 |
| Borderline Pumping Temperature | D 3829 | °C | -42 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 T 800 10W-30 is **1.39** kg CO_2 eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product. For more info check here

