

Q8 T 800 10W-40

Synthetic based API CI-4 and ACEA E7 heavy-duty engine oil

Description

Q8 T 800 10W-40 is a super high performance heavy-duty engine oil which offers optimum engine durability and prevents deposit formation. This lubricant provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs and prevents corrosion and foaming. It meets the requirements of API CI-4 and ACEA E7.

Applications

 $Q8\ T\ 800\ 10W\text{-}40\ is\ designed\ for\ normally\ aspirated, turbocharged, or\ supercharged\ engines,\ with\ or\ without\ intercooling.\ It\ is\ normally\ aspirated\ for\ normall\ for\$ recommended for most heavy-duty diesel engines for on- and off highway applications. It meets the ACEA E7 and API CI-4 specification as well as the requirements of MAN, MB, Volvo, Caterpillar, Cummins and MTU. Can also be used for Passenger Cars requiring API SL.

Benefits

- Premium protection against engine wear.
- Advanced engine protection after cold start.
- High protection against piston rings deposits.
- High protection against rust and corrosion.

Specifications, recommendations and approvals

ACEA	E7	Daimler Truck AG	DTFR 15B110 (MB 228.3)
API	CI-4	Deutz	DQC III-10
API	SL	Global	DHD-1
Caterpillar	ECF-1	MAN	M 3275-1
Caterpillar	ECF-2	мти	Type 2
Cummins	CES 20071	Mack	EO-N
Cummins	CES 20072	Renault	RLD
Cummins	CES 20076	Renault	RLD-2
Cummins	CES 20077	Tedom	258-3
Cummins	CES 20078	Volvo	VDS-3

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.876
Viscosity Grade	-	-	SAE 10W-40
Kinematic Viscosity, 40 °C	D 445	mm²/s	98.0
Kinematic Viscosity, 100 °C	D 445	mm²/s	14.3
Viscosity Index	D 2270	-	153
Total Base Number	D 2896	mg KOH/g	10.5
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	232
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 T 800 10W-40 is **1.46** kg CO $_2$ eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product. For more info check here

