

## Q8 Auto 15 A

Full synthetic automatic transmission fluid Allison transmissions requiring Allison TES-668, TES-295 and TES-389.

### Description

Q8 Auto 15 A is a superior performance full synthetic automatic transmission fluid, designed for heavy duty vehicles. The product is especially formulated for trucks, buses and military equipment in severe operating conditions, because of its exceptional viscosity index and extended drain capability. It is approved for Allison transmission specification A668.

### Applications

Q8 Auto 15 A is specifically formulated for severe operating conditions. It is specifically designed for Allison transmissions approved Allison TES-668 and backwards compatible to Allison TES-295 and Allison TES-389, Recommended for use in Allison 1000 Series™, 2000 Series™, 3000 Series™, 4000 Series™, H 40/50 EP™ and eGen Flex™

### Benefits

- Exceptional drain interval extension.
- Maximum protection against equipment component corrosion.
- Full synthetic formulation to provide an extreme thermal stability.
- Improved shear stability for a stable viscosity during use

### Specifications, recommendations and approvals

Allison	TES-295	Ford	XT-2-QDX
Allison	TES-389	Ford	XT-5-QM
Allison	TES-468TM	GM	Dexron III H
Allison	<b>TES-668</b>	JASO	M315 Type 1A
DANA	OHTM-TO	MAN	339 Type V1
Daimler Truck AG	DTFR 13C180 (MB 236.91)	Voith	H55.6335.xx
Daimler Truck AG	DTFR 13C190 (MB 236.92)		

Color code blue = officially approved

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,852
Density, 15 °C	D 4052	g/ml	0.849
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	34.4
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	6.8
Viscosity Index	D 2270	-	165
Brookfield Viscosity, -40 °C	D 2983	Pa.s	10
Pour Point	D 97	°C	-51
Flash Point, COC	D 92	°C	210

The figures above are not a specification. They are typical figures obtained within production tolerances.