

Q8 Handel 32

Zinc-based hydraulic oil with very high viscosity index

Description

Q8 Handel 32 is an excellent zinc-based hydraulic oil that is suitable for a wide range of temperatures and applications. Thanks to its very high viscosity index of >180, the zinc-based oil has exceptional flow properties. The high oxidation stability assures an extended drain interval and lubricant life. Q8 Handel 32 is used in demanding applications that require very high viscosity index oils.

Applications

Q8 Handel 32 is used in all season applications, off-highway equipment. It is also applied in industries and applications requiring high viscosity index oils, such as in paper, steel, cement, mining industry.

Benefits

- Lower downtime and an improved maintenance efficiency
- Zinc included technology
- Exceptionally high viscosity index
- Optimum air release
- Outstandingly resistant to oil deterioration
- Exceptionally suitable for use in all seasons
- Optimum separation of water

Specifications & Approvals

 Bosch Rexroth
 RE 90220 notes
 ISO
 11158 HV

 DIN
 51524-3 HVLP
 Swedish Standard
 SS 155434 AV

Eaton Brochure 03-401-2010

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0,872
Density, 20 °C	D 4052	g/ml	0,863
Colour	D 1500	-	L 1.0
Kinematic Viscosity, 40 °C	D 445	mm²/s	32
Kinematic Viscosity, 100 °C	D 445	mm²/s	7
Viscosity Index	D 2270	-	180
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	190
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(15 min)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Handel 32 is **1.35** kg CO $_2$ eq / kg. Please contact Q80ils to learn more about the positive environmental impact, the

handprint, of this product. For more info check here

