

## Q8 Rubens EM 2

Lithium complex grease for electric motor bearings

### Description

Q8 Rubens EM 2 is a lithium complex grease and the primary choice for different types of electric motor bearing applications. The mineral oil-based grease is used in a wide temperature range and has outstanding low start-up torque properties. Q8 Rubens EM 2 has outstanding roll and mechanical stability and an excellent rust-protection. Its smooth structure leads to an easy pumpability.

### Applications

Q8 Rubens EM 2 is used as a versatile grease for a variety of industrial applications. It is highly recommended for bearing lubrication of electric motors and high speed applications.

### Benefits

- Extensive oil drain interval for a longer lubricant lifetime
- Minimizes downtime which leads to a higher maintenance efficiency
- Excellently high dropping point
- Superior anti-rust characteristics
- Excellently suitable for applications in a broad temperature spectrum
- Outstanding roll stability
- Excellent high load carrying capacity
- Optimum grease flow properties

### Specifications & Approvals

**DIN** 51502 KP2N-30 **ISO** 6743 L-XCDHB2

### Properties

	Method	Unit	Typical
Soap type	-	-	Lithium complex
Colour	Visual	-	Yellowish
Consistency, NLGI No.	NLGI	-	2
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	295
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	110
Dropping Point	D 566	°C	>260
Copper Corrosion, 100 °C, 24 h	D 4048	-	1b
Four Ball Test, Weld Load	IP 239	N	2600
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.