

Q8 Stravinsky N 46

High performance refrigeration compressor oil

Description

Q8 Stravinsky N 46 is a high performance refrigeration compressor oil. It is developed with premium selected naphtenic base fluid. The product is recommended for use with CFC-, HCFC- or traditional type refrigerant (such as ammonia). The low pour point and outstanding fluidity at low temperature ensure problem-free operations.

Applications

Reciprocating- and rotary refrigerator compressors Industrial applications such as refrigerators and freezers Refrigerating systems handling CFC-, HCFC- or traditional type refrigerant (such as ammonia)

Features

Enhanced technology

Benefits

Fully compatible with mineral oils and normally used elastomer/plastic materials in compressor equipment

Extended drain

Advanced oxidative stability, guaranteeing long oil life under continuous and severe operating conditions

Safety

Tailored to the specific needs of your equipment to ensure safe and reliable operations

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	909
Kinematic Viscosity, 40 °C	D 445	mm ² /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	5.6
Flash Point, COC	D 92	°C	190

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky N, it is recommended to flush the compressor lubricant system.