

## Q8 SuperGear M 75W-80

Synthetic transmission fluid

### Description

Q8 SuperGear M 75W-80 is a superior synthetic transmission fluid, offering extended drain intervals and best-in-class performance in demanding conditions. This product provides easy gear shifting and exceptional protection in high temperatures due to constant film strength. Its low viscosity characteristics optimize transmission efficiency and fuel economy.

### Applications

Q8 SuperGear M 75W-80 meets the requirements of many commercial vehicle OEMs and/or gearbox manufacturers including MAN, Mercedes-Benz, Voith, Eaton and Volvo.

### Benefits

- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.

### Specifications, recommendations and approvals

API	GL-4	MB	235.29 (DTFR 13D120)
Eaton/Fuller		Voith	Class C Retarder Oil
MAN	341 Type E4	Volvo	97307 (400.000 km)
MAN	341 Type VR		

Color code blue = officially approved

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,86
Viscosity Grade	-	-	SAE 75W-80
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	65.9
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	10.5
Viscosity Index	D 2270	-	149
Brookfield Viscosity, -40 °C	D 2983	Pa.s	32.0
Pour Point	D 97	°C	-55
Flash Point, P-M	D 93	°C	188

The figures above are not a specification. They are typical figures obtained within production tolerances.