

Q8 da Vinci 6

Light demoulding oil with exceptional surface finishing

Description

Q8 da Vinci 6 is a superior demoulding oil with anti-rust inhibitors for steel moulds. It's solvent free and easily applicable. The reactive layer in the oil creates a layer between the concrete and the mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci provides an exceptional smooth surface finish of the concrete and a clean mould without staining or dust.

Applications

Q8 da Vinci 6 is used for demoulding concrete foundation piles, tiles and on-site elements such as floors, stairs, balconies and prefab sewage pipes. It is applied in steel and plywood moulds. Q8 da Vinci 6 is highly recommended on site building constructions for direct release demoulding.

Benefits

- Leads to an improved durability of the finished product quality
- Outstanding quality of the surface
- Extremely effective demoulding operation
- · Light colour
- Exceptional anti-rust properties
- · Enhanced with special additives
- Prevents sticking
- Extremely handy to apply

Properties

	Method	Unit	Typical	
Appearance	Visual	-	Bright and Clear	
Density, 15 °C	D 4052	g/ml	0,836	
Kinematic Viscosity, 40 °C	D 445	mm²/s	6.0	
Pour Point	D 97	°C	-21	
Flash Point, COC	D 92	°C	130	
Rust Test, Proc. A and B, 24 h	D 665	-	pass	

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

For use in cold temperatures, we recommend Q8 da Vinci P series. Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 da Vinci 6 is 1.26 kg CO₂eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here

