

Q8 Antifreeze Long Life OAT Premixed

Superior premixed long life antifreeze

Description

Q8 Antifreeze Long Life OAT Premixed is a superior fluid that protects against freezing, boiling and corrosion of the cooling system. The antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Q8 Antifreeze Long Life OAT Premixed is obtained by non-depleting corrosion inhibitors.

Applications

Q8 Antifreeze Long Life OAT Premixed is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Benefits

- Best-in-class cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.
- Exceptional long life protection against all forms of corrosion.
- Superior and extended corrosion protection due to synergistic effects.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime

Specifications, recommendations and approvals

AGCO		Iveco	18-1830
Cummins	CES 14439	Leyland Trucks	DW03245403
Cummins	CES 14603	MAN	324 Type SNF
DAF	74002	MAN	325 Type SNF
Daimler Truck AG	DTFR 29C110 (MB 325.3)	Renault	41-01-001/- -S Type D
Daimler Truck AG	DTFR 29D110 (MB 326.3)	Renault	41-01-001/- -T
Detroit Diesel	93K217	Rolls-Royce Bergen	2.13.01
Detroit Diesel	DFS 93K227	Stellantis	FPW 9.55523
Deutz	DQC CB-14	Stellantis	GMW 18270
Ford	M97B44-D	Stellantis	GMW 3420
Foton	Q-FPT 2313005-2013	Tedom	
GM	B 040 1065	VAG	VW TL 774 D (G12)
GM	GMW 18270	VAG	VW TL 774 F (G12+)
GM	GMW 3420	Wärtsilä	
Isuzu			

Properties

	Method	Unit	Typical
Density, 20 °C	D 1122	kg/l	1.072
Colour	Visual	-	orange/red
Freezing Protection 50-50%	D 1177	°C	-37
Equilibrium Reflux Boiling Point	D 1120	°C	109
pH	D 1287	-	8.7

The figures above are not a specification. They are typical figures obtained within production tolerances.