

## Q8 Brake Fluid DOT 5.1

High performance Long Life Fully Synthetic Brake Fluid DOT 5.1.

### Description

Q8 Brake Fluid DOT 5.1 is a high performance Long Life Fully Synthetic Brake Fluid recommended for all types of hydraulic actuated brake & clutch systems, Especially designed for anti-locking braking systems (ABS). This non-silicone base fluid is designed with accordance with DOT 5.1, and fulfils also DOT 4 and DOT 2 manufacturers' recommendations. Formulated for best results in safe braking at most severe conditions

### Applications

Q8 Brake Fluid DOT 5.1 have been designed for application in all vehicles and motorcycles recommending DOT 5.1 specification brake fluid. Mixable with DOT 4 and DOT 3, do not mix with silicone or mineral base fluids.

### Specifications, recommendations and approvals

FMVSS	116 DOT 3	ISO	4925 Class 5.1
FMVSS	116 DOT 4	SAE	J 1703
ISO	4925 Class 4	SAE	J 1704

### Properties

	Method	Unit	Typical
Kinematic Viscosity, -40 °C	D 445	mm <sup>2</sup> /s	900
Wet Equilibrium Reflux Boiling Point	FMVSS 116	°C	180
Dry Equilibrium Reflux Boiling Point	FMVSS 116	°C	260

The figures above are not a specification. They are typical figures obtained within production tolerances.