

Q8 Formula Truck 8510 10W-40

Synthetic Ultra High Performance Diesel engine oil meeting ACEA E8 / E6 / E11 / E9 / E7 and API CK-4 / CJ-4 for off-road applications

Description

Q8 Formula Truck 8510 10W-40 is a superior ultra high performance low SAPS heavy-duty engine oil. This product is bio-fuel compatible and has excellent cold starting properties. It offers extended oil drains, provides exceptional protection against wear and prevents oxidation. It meets requirements of OEM's such as Mercedes-Benz, MAN, Scania and Volvo.

Applications

Q8 Formula Truck 8510 10W-40 is developed for heavy-duty vehicles requiring the ACEA E6 / E7 / E8 / E9 / E11 and API CK-4 specifications. It can be used in most Euro IV, Euro V and Euro VI diesel engines equipped with after treatment systems and operating on low sulphur diesel. It exceeds the requirements of more than 90% of the heavy-duty fleet such as Scania, MAN, Mercedes-Benz, Cummins, Volvo, MTU or Caterpillar.

Specifications / Recommendations / Approvals

ACEA	E11 / E 9	Liebherr	LH-00-ENG5C LA
ACEA	E7	MAN	M 3271-1
ACEA	E8 / E6	MAN	M 3477
API	CJ-4 / SN	MAN	M 3575
API	CK-4	MAN	M 3775
Caterpillar	ECF-3	MB	228.31 (DTFR 15C100)
Cummins	CES 20081	MB	228.51 (DTFR 15C110)
Cummins	CES 20086	MB	228.52 (DTFR 15C120)
DAF	Extended Drain	MTU	Type 2.1
Daimler Truck AG	DTFR 15C100 (MB 228.31)	MTU	Type 3.1
Daimler Truck AG	DTFR 15C110 (MB 228.51)	Mack	EO-O Premium Plus
Daimler Truck AG	DTFR 15C120 (MB 228.52)	Mack	EO-S 4.5
Detroit Diesel	DFS 93K218 / 93K222	Renault	RGD
Deutz	DQC IV-18 LA	Renault	RLD-3
Iveco	18-1804 TLS E6	Scania	LA (Low Ash)
Iveco	18-1804 TLS E9	Volvo	CNG
JASO	DH-2	Volvo	VDS-4
Liebherr	LH-00-ENG LA	Volvo	VDS-4.5
Liebherr	LH-00-ENG3A LA		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	10W-40
Density, 15 °C	D 4052	g/ml	0.871
Density, 20 °C	D 4052	g/ml	0.868
Kinematic Viscosity, 40 °C	D 445	mm ² /s	102.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.8
Viscosity Index	D 2270	-	150
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	238
Total Base Number	D 2896	mg KOH/g	10
Sulfated Ash	D 874	% mass	1.0%

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Truck 8510 10W-40 is **1.32** kg CO₂eq / kg.*

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**