

## Q8 Formula Truck 8900 FE 10W-30

Synthetic Ultra High Performance Diesel engine oil meeting ACEA E8 / E6 / E11 / E9 / E7

### Description

The Q8 Formula Truck 8900 FE 10W-30 is a superior ultra high performance low SAPS heavy-duty engine oil. This product offers exceptional protection against engine wear, specifically against cam wear, and provides fuel economy improvements up to 1% or more. It meets ACEA E6 specification along with specifications of various leading European OEM's such as Mercedes-Benz, MAN, Scania and Volvo.

### Applications

Q8 Formula Truck 8900 FE 10W-30 is developed for heavy-duty vehicles requiring the ACEA E6/E7/E8/ E9/E11 and API CK-4 specifications. It can be used in most Euro IV, Euro V and Euro VI diesel engines equipped with after treatment systems and operating on low sulphur diesel fuel. It exceeds the requirements of more than 90% of the heavy-duty fleet such as IVECO, Scania, MAN, Mercedes-Benz, Cummins, Volvo, MTU or Caterpillar.

### Benefits

- Superior protection against engine wear.
- Fuel economy improvement up to 1%.
- Superior catalytic after treatment system (SCR) protection.
- Exceptional engine protection after cold start.
- Best-in-class engine cleanliness.

### Specifications / Recommendations / Approvals

ACEA	E11 / E 9	JASO	DH-2
ACEA	E7	Liebherr	LH-00-ENG LA
ACEA	E8 / E6	Liebherr	LH-00-ENG3A LA
API	CJ-4 / SN	MAN	M 3477
API	CK-4	MAN	<b>M 3677</b>
Caterpillar	ECF-3	MAN	<b>M 3775</b>
Cummins	CES 20081 / 20086	MB	226.9
DAF	PSQL 2.1E	MB	227.61 (DTFR 15D100)
DAF	PSQL 2.1E LD	MTU	Type 3.1
DAF	PSQL 2.4	Mack	<b>EO-S 4.5</b>
Daimler Truck AG	<b>DTFR 15C100 (MB 228.31)</b>	Renault	RGD
Daimler Truck AG	<b>DTFR 15C110 (MB 228.51)</b>	Renault	<b>RLD-3</b>
Daimler Truck AG	<b>DTFR 15C120 (MB 228.52)</b>	Scania	LA (Low Ash)
Detroit Diesel	DFS 93K218 / 93K222	Volvo	CNG
Deutz	<b>DQC IV-18 LA</b>	Volvo	VDS-4
Iveco	18-1804 TLS E9	Volvo	<b>VDS-4.5</b>

Color code blue = officially approved

## Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	10W-30
Density, 15 °C	D 4052	g/ml	0,861
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	74.3
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	12.3
Viscosity Index	D 2270	-	164
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	221
Total Base Number	D 2896	mg KOH/g	10.1
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Truck 8900 FE 10W-30 is **1.40** kg CO<sub>2</sub>eq / kg.  
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here

