

Q8 Garden Pro Synt 4T 5W-30

Superior garden oil

Description

Q8 Garden Pro Synt 4T 5W-30 is a superior synthetic multigrade lubricant for garden equipment. It guarantees an exceptional performance in both air and water cooled engines. Q8 Garden Pro Synt 4T 5W-30 has been enriched with unique components that improve lubricity and enhance detergency and cleanliness. The reliable garden oil offers an extreme wear protection.

Applications

Q8 Garden Pro Synt 4T 5W-30 is used in all 4-stroke gasoline engines of garden equipment such as lawn mowers, rider mowers and snow blowers. It is a reliable lubricant that covers a broad range of applications and can be used in the most severe conditions.

Specifications, recommendations and approvals

API	CF	API	SL

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,851
Viscosity Grade	-	-	5W-30
Kinematic Viscosity, 40 °C	ISO 3104	mm²/s	64.3
Kinematic Viscosity, 100 °C	D 445	mm²/s	11.3
Viscosity Index	D 2270	-	169
Apparent Viscosity, -30 °C	D 5293	mPa.s	4300
Flash Point, P-M	D 93	°C	237
Pour Point	D 97	°C	-36
Sulfated Ash	D 874	% mass	1.2

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Garden Pro Synt 4T 5W-30 is **1.34** kg CO₂eq / kg.
Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here

