

SAFETY DATA SHEET

Q8 Hindemith 15



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Q8 Hindemith 15

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for hydraulic equipment

1.3 Details of the supplier of the safety data sheet

Supplier : Kuwait Petroleum Companies in the Benelux
Company Office: Brusselstraat 59, 2018 Antwerp, Belgium
Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium
Tel. +32 3 247 38 11, Fax +32 3 216 03 42

Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.l.
Petroleumkaai 7 Via Volpedo 2
B-2020 Antwerp 15050 Castellar Guidobono (AL)
Belgium Italy

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

PCN Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670

Global (English only) : +44 (0) 1865 407 333

National advisory body/Poison Center

Belgium : Poison Centre : +32 (0)70 245 245



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

ASPIRATION HAZARD

Category 1

H304

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



SECTION 2: Hazards identification

| | |
|---|--|
| Signal word | : Danger |
| Hazard statements | : H304 - May be fatal if swallowed and enters airways. |
| Precautionary statements | |
| Prevention | : Not applicable. |
| Response | : P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. |
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics |
| Supplemental label elements | : Contains methyl methacrylate and N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl) amine. May produce an allergic reaction. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| Detergents - Regulation (EC) No 648/2004 | : Not applicable. |
| Special packaging requirements | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : Prolonged or repeated contact may dry skin and cause irritation. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|---|---|-----------|---|---|---------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | REACH #: 01-2120920648-49 EC: 954-225-2 | ≥75 - ≤90 | Asp. Tox. 1, H304 | - | [1] [2] |
| Severely refined mineral oil (C15 - C50) * - H304 | - | ≤10 | Asp. Tox. 1, H304 | - | [1] [2] |
| methyl methacrylate | REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6 | ≤0.3 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335 | - | [1] [2] |
| N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl) amine | REACH #: 01-2119930450-49 01-0000015116-78 | <0.1 | Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 | - | [1] |

Q8 Hindemith 15

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|---|--|---|--|--|
| | EC: 401-280-0 CAS: 91273-04-0 Index: 613-072-00-9 | | Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above. | | |
|--|---|--|---|--|--|

* Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. High pressure skin injections are serious medical emergencies. Injury will not appear serious at first. Within a few hours, tissue will become swollen, discolored and extremely painful.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.

SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Exposure limit values |
|---|--|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | Limit values (Belgium, 5/2021). [] TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist |
| Severely refined mineral oil (C15 - C50) * - H304 | Limit values (Belgium, 5/2021). [] TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist |
| methyl methacrylate | EU OEL (Europe). TWA: 5 mg/m ³ 8 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist Limit values (Belgium, 5/2021). TWA: 50 ppm 8 hours. TWA: 208 mg/m ³ 8 hours. STEL: 416 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|---|-----------------------|-------------------------|--------------------|--------------------|
| methyl methacrylate | DNEL | Long term Oral | 8.2 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 208 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 416 mg/m ³ | Workers | Local |
| | DNEL | Short term Dermal | 1.5 mg/cm ² | General population | Local |
| | DNEL | Long term Dermal | 1.5 mg/cm ² | General population | Local |
| | DNEL | Short term Dermal | 1.5 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 1.5 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 8.2 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 13.67 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 74.3 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 104 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 208 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 348.4 mg/m ³ | Workers | Systemic |
| | N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl)amine | DNEL | Long term Oral | 0.25 mg/kg bw/day | General population |

Q8 Hindemith 15

SECTION 8: Exposure controls/personal protection

| | | | | | |
|--|------|----------------------|------------------------|--------------------|----------|
| | DNEL | Long term Dermal | 0.25 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 0.43 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 0.5 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 1.76 mg/m ³ | Workers | Systemic |

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Do not ingest. If swallowed then seek immediate medical assistance.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Oily liquid.]

Appearance : Clear.

Color : Yellow [Light]

Q8 Hindemith 15

SECTION 9: Physical and chemical properties

| | |
|--|---|
| Odor | : Characteristic. |
| Odor threshold | : Not available. |
| Melting point/freezing point | : Not applicable. |
| Pour point | : <-42°C (<-43.6°F) [ASTM D 97] |
| Initial boiling point and boiling range | : >200°C (>392°F) |
| Flammability | : Not applicable. |
| Lower and upper explosion limit | : Not available. |
| Flash point | : Open cup: >100°C (>212°F) [ASTM D92.] |
| Auto-ignition temperature | : >300°C (>572°F) |
| Decomposition temperature | : >200°C |
| pH | : Not applicable. |
| Viscosity | : Kinematic (40°C (104°F)): 15 mm ² /s (15 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 5.6 mm ² /s (5.6 cSt) [ASTM D 445] |
| Solubility(ies) | : |

| Media | Result |
|------------|-------------|
| cold water | Not soluble |
| hot water | Not soluble |

| | |
|--|--|
| Solubility in water | : Not available. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapor pressure | : <0.01 kPa (<0.075006 mm Hg) |
| Density | : 0.87 g/cm ³ [15°C (59°F)] [ASTM D 4052] |
| Vapor density | : Not available. |
| Explosive properties | : Not applicable. |
| Oxidizing properties | : Not applicable. |
| <u>Particle characteristics</u> | |
| Median particle size | : Not applicable. |

9.2 Other information

9.2.1 Information with regard to physical hazard classes

| | |
|-----------------------------|-------------------|
| Explosive properties | : Not applicable. |
| Oxidizing properties | : Not applicable. |

9.2.2 Other safety characteristics

SECTION 10: Stability and reactivity

| | |
|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : Reactive or incompatible with the following materials: Strong oxidizing materials |

Q8 Hindemith 15

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|--------------------|-------------------------|----------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | LC50 Inhalation Dusts and mists | Rat | 5.28 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >1700 mg/kg | - |
| | LD50 Oral | Rat | >4150 mg/kg | - |
| Severely refined mineral oil (C15 - C50) * - H304 | LC50 Inhalation Dusts and mists | Rat - Male, Female | 5.53 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| methyl methacrylate | LC50 Inhalation Vapor | Rat | 78000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | 7872 mg/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | N/A | N/A | N/A | N/A | 5.28 |
| Severely refined mineral oil (C15 - C50) * - H304 | N/A | N/A | N/A | N/A | 5.53 |
| methyl methacrylate | 7872 | N/A | N/A | 78 | N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|------------------------------------|---------|-------|----------|-------------|
| Severely refined mineral oil (C15 - C50) * - H304 | Eyes - Iris lesion | Rabbit | 0 | 48 hours | 72 hours |
| | Eyes - Redness of the conjunctivae | Rabbit | 0.33 | 48 hours | 72 hours |
| | Skin - Edema | Rabbit | 0 | 72 hours | 7 days |
| | Skin - Erythema/Eschar | Rabbit | 0.17 | 72 hours | 7 days |

Conclusion/Summary : Not available.

Sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) * - H304 | skin | Guinea pig | Not sensitizing |

Conclusion/Summary : Not available.

Mutagenicity

| Product/ingredient name | Test | Experiment | Result |
|---|---|---|----------|
| Severely refined mineral oil (C15 - C50) * - H304 | 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic | Negative |

Conclusion/Summary : Not available.

Carcinogenicity

Q8 Hindemith 15

SECTION 11: Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|------------------------|----------------|------|----------|
| Severely refined mineral oil (C15 - C50) * - H304 | Negative - Dermal - TC | Mouse - Female | - | 78 weeks |

Conclusion/Summary : Not available.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|---|-------------------|-----------|-------------------|--------------------|------------------|----------|
| Severely refined mineral oil (C15 - C50) * - H304 | Negative | Negative | Negative | Rat - Male, Female | Oral: 1000 mg/kg | - |

Conclusion/Summary : Not available.

Teratogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------------|---------|------------|-----------------|
| Severely refined mineral oil (C15 - C50) * - H304 | Negative - Dermal | Rat | 2000 mg/kg | 7 days per week |

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| methyl methacrylate | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Product/ingredient name | Result |
|--|--|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics Severely refined mineral oil (C15 - C50) * - H304 | ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Q8 Hindemith 15

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|------------------------------------|--------------------|------------------------|---------------------------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | Sub-chronic NOAEL Dermal | Rat | >495 mg/kg | - |
| | Sub-chronic NOAEL Oral | Rat | >1056 mg/kg | - |
| Severely refined mineral oil (C15 - C50) * - H304 | Sub-chronic NOAEL Inhalation Vapor | Rat | 3950 mg/m ³ | 6 hours; 5 days per week |
| | Sub-acute LOAEL Oral | Rat - Male | 125 mg/kg | 13 weeks; 5 hours per day |
| | Sub-chronic NOAEL Oral | Rat - Male, Female | ≥2000 mg/kg | 13 weeks; 5 days per week |
| | Sub-acute NOAEL Inhalation Vapor | Rat - Male | >980 mg/m ³ | 4 weeks; 5 days per week |

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|------------------------------------|---|----------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | EC50 >1000 mg/l | Daphnia | 48 hours |
| | LC50 >1000 mg/l | Fish | 96 hours |
| Severely refined mineral oil (C15 - C50) * - H304 | Acute NEL >100 mg/l Fresh water | Algae | 72 hours |
| | Acute NEL >10000 mg/l Fresh water | Daphnia - <i>Daphnia Magma</i> | 48 hours |
| methyl methacrylate | Acute NEL ≥100 mg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |
| | Chronic NEL 10 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 21 days |
| | Acute LC50 130000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> - Adult | 96 hours |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Q8 Hindemith 15

SECTION 12: Ecological information

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | - | - | Inherent |
| Severely refined mineral oil (C15 - C50) * - H304 | - | - | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---|--------------------|-----|-----------|
| Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics | >3 | - | Low |
| methyl methacrylate | 1.38 | - | Low |
| N,N-bis(2-ethylhexyl)-(1,2,4-triazol-1-yl)methyl amine | 5.3 | - | High |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|--|
| 13 01 10* | mineral based non-chlorinated hydraulic oils |

Packaging





Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Q8 Hindemith 15

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|--|--|--|--|
| 14.1 UN number or ID number | UN3082 | UN3082 | UN3082 | UN3082 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ethyl 3-[[bis(1-methylethoxy) phosphinothioyl]thio] propionate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ethyl 3-[[bis(1-methylethoxy) phosphinothioyl]thio] propionate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ethyl 3-[[bis(1-methylethoxy) phosphinothioyl]thio] propionate) | Environmentally hazardous substance, liquid, n.o.s. (ethyl 3-[[bis(1-methylethoxy) phosphinothioyl]thio] propionate) |
| 14.3 Transport hazard class(es) | 9  | 9  | 9  | 9  |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. | Yes. |

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Hazard identification number 90

Limited quantity 5 L

Special provisions 274, 335, 601, 375

Tunnel code (-)

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Special provisions 274, 335, 375, 601

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F

Special provisions 274, 335, 969

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964.

Special provisions A97, A158, A197, A215

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Q8 Hindemith 15

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name | % | Designation [Usage] |
|-------------------------|-------|---------------------|
| Q8 Hindemith 15 | ≥90 | 3 |
| 4-nonylphenol, branched | <0.01 | 46 |

Labeling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Germany

Hazard class for water (WGK) : 1

Switzerland

VOC content : VOC (w/w): 84.3%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Q8 Hindemith 15

SECTION 15: Regulatory information

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

| | |
|---------------------------------|--|
| Australia | : All components are listed or exempted. |
| Canada | : At least one component is not listed. |
| China | : All components are listed or exempted. |
| Eurasian Economic Union | : Russian Federation inventory : Not determined. |
| Japan | : Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined. |
| New Zealand | : All components are listed or exempted. |
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States of America | : All components are active or exempted. |
| Viet Nam | : Not determined. |

15.2 Chemical Safety Assessment : Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

Exposure Scenario information : This product has been assessed according to the REACH regulation. Addition of an Exposure Scenario is not required. All Risk Management Measures of the contained substances are covered by the main body of this Safety Data Sheet.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ASTM = American Society for Testing and Materials
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- CAS = Chemical Abstracts Service
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DIN = German Institute for Standardization
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EC = European Commission
- EC50 = Half maximal effective concentration
- EN = European Standard (Norm)
- EUH statement = CLP-specific Hazard statement
- GHS - Globally Harmonized System of Classification and Labeling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IC50 = Half maximal inhibitory concentration
- IMDG = International Maritime Dangerous Goods
- IMO = International Maritime Organisation
- ISO = International Organization for Standardization

SECTION 16: Other information

LC50 = Median lethal concentration
 LD50 = Median lethal dose
 LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
 NOEL / NOEC = No Observed Effect Level / Concentration
 OECD = Organisation for Economic Co-operation and Development
 OEL = Occupational Exposure Limit
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS = Safety Data Sheet
 SVHC = Substances of Very High Concern
 STEL = Short Term Exposure Limit
 TLV = Threshold Limit Value
 TWA = Time Weighted Average
 UFI = Unique Formula Identifier
 UN = United Nations
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------|--------------------|
| Asp. Tox. 1, H304 | Calculation method |

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

| | |
|------|--|
| H225 | Highly flammable liquid and vapor. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Full text of classifications [CLP/GHS]

| | |
|-------------------|---|
| Aquatic Chronic 2 | AQUATIC HAZARD (LONG-TERM) - Category 2 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1A | SKIN SENSITIZATION - Category 1A |
| Skin Sens. 1B | SKIN SENSITIZATION - Category 1B |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3 |

Training advice : Ensure operatives are trained to minimise exposures.

Date of printing : 03-10-2023

Date of issue/ Date of revision : 03-10-2023

Q8 Hindemith 15

SECTION 16: Other information

Date of previous issue : 01-05-2023
Version : 1.09
Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.