

## Q8 Mineral SAE 40

Mineral API CF-4 heavy-duty engine oil

### Description

Q8 Mineral SAE 40 is a four-stroke heavy-duty diesel engine oil. This product provides good lubrication after cold starting and thus limits engine wear, prohibits corrosion and protects against rust. It exceeds the normal standards of piston cleanliness for API CF-4.

### Applications

Q8 Mineral SAE 40 can be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment. It can be used where API CF-4 is required. To be used where monograde engine oil is preferred

### Benefits

- Premium protection against engine wear.
- High protection against piston rings deposits.
- High protection against rust and corrosion.

### Specifications, recommendations and approvals

API

CF

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.892
Viscosity Grade	-	-	SAE 40
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	125
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.8
Viscosity Index	D 2270	-	105
Total Base Number	D 2896	mg KOH/g	8.5
Pour Point	D 97	°C	-15
Flash Point, P-M	D 93	°C	212
Sulfated Ash	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.