

Q8 T 750 SAE 50

Mineral API CI-4 and ACEA E7 heavy duty engine oil

Description

Q8 T 750 SAE 50W is a heavy duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7.

Applications

Q8 T 750 SAE 50W for commercial vehicles, buses, off-highway/construction or military equipment. To be used where monograde engine oil is preferred in some transmission applications.

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

ACEA	A3/B4	API	CI-4
ACEA	E3	API	SL
ACEA	E5	MTU	Type 1
ACEA	E7		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,893
Viscosity Grade	-	-	SAE 50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	200
Kinematic Viscosity, 100 °C	D 445	mm ² /s	18.0
Viscosity Index	D 2270	-	103
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	204
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 SAE 50 is **1.33** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**