

Q8 Terra 4000 UTTO CVT 75W-85

Exceptional Synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 Terra 4000 UTTO CVT 75W-85 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T Q8 Terra 4000 UTTO CVT 75W-85 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 Terra 4000 UTTO CVT 75W-85 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

Benefits

- Superior viscosity retention providing smoothless CVT operation.
- Best-in-class oxidation stability.
- Superior frictional properties for smooth brake operation.
- Superior response of hydraulic components.
- Maximum compatibility with conventional elastomers.

Specifications, recommendations and approvals

AGCO	CVT ML 200	Same Deutz Fahr	UTTO
API	GL-4	Valtra	G2-08 (XT-60)
Case	MS 1207 / MS 1209	Valtra	G2-B10 (XT-60+)
Case	MS 1210	ZF	TE-ML 03E / 03G / 03L
Case New Holland	MAT 3505	ZF	TE-ML 05F
Case New Holland	MAT 3525 / MAT 3540	ZF	TE-ML 06B
Case New Holland	MAT 3541 / MAT 3544	ZF	TE-ML 06D
Case New Holland	MAT 3552-A / MAT 3553-A	ZF	TE-ML 06E
Caterpillar	SATO	ZF	TE-ML 06F
Claas	CVT	ZF	TE-ML 06K
Deutz	Allis AC Power Fluid 821 XL	ZF	TE-ML 06L
Fendt	FWN 81001	ZF	TE-ML 06M
Fendt	Vario	ZF	TE-ML 06N
John Deere	JDM J20C	ZF	TE-ML 06P
Komatsu	KES 07.866	ZF	TE-ML 06R
Kubota	UDT / Super UDT / UDT-HD	ZF	TE-ML 06S
Massey Ferguson	CMS M 1135	ZF	TE-ML 06T
Massey Ferguson	CMS M 1141 / M 1143 / M 1145	ZF	TE-ML 17E
New Holland	NH 410-B / NH 410-C	ZF	TE-ML 21F

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	10W-30
Viscosity Grade	SAE J306	SAE	75W-85
Density, 15 °C	D 4052	g/ml	0,861
Density, 20 °C	D 4052	g/ml	0,858
Kinematic Viscosity, 40 °C	D 445	mm ² /s	71.1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.0
Viscosity Index	D 2270	-	166
Brookfield Viscosity, -20 °C	D 2983	mPa.s	3400
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	240

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT 75W-85 is **1.30** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**