

## Q8 Auto 14

Automatic transmission fluid

### Description

Q8 Auto 14 is an advanced transmission fluid for various applications, mainly heavy duty. The product is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems.

### Applications

Q8 Auto 14 is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems. It is suitable for automatic transmissions in most passenger cars, buses, construction and military equipment and in selected manual transmissions, but also as power steering and hydraulic fluid. It meets ZF, Voith, Allison, Volvo, Ford, MAN and MB specifications.

### Benefits

- Advanced protection against wear and extends component life.
- High protection against rust and corrosion.
- Cold starting improvement.

### Specifications, recommendations and approvals

|                 |                     |       |                      |
|-----------------|---------------------|-------|----------------------|
| Allison         | C-4                 | MB    | 236.5                |
| Ford            | M2C138-CJ           | MB    | 236.7 (DTFR 13C140)  |
| Ford            | M2C166-H            | Voith | <b>H55.6335.xx</b>   |
| Ford            | M2C185-A            | Voith | <b>US SB 013/118</b> |
| Ford            | M2C186-A            | Volvo | 97325                |
| GM              | 6137M               | Volvo | 97335                |
| GM              | Dexron II D         | Volvo | 97340                |
| Iveco           | 18-1807 AG2         | ZF    | TE-ML 02F            |
| Komatsu Dresser | B22-0004            | ZF    | TE-ML 03D            |
| MAN             | <b>339 Type L2</b>  | ZF    | <b>TE-ML 04D</b>     |
| MAN             | <b>339 Type V1</b>  | ZF    | TE-ML 09             |
| MAN             | <b>339 Type Z1</b>  | ZF    | <b>TE-ML 14A</b>     |
| MB              | 236.1 (DTFR 13C100) | ZF    | TE-ML 17C            |

Color code blue = officially approved

### Properties

|                              | Method | Unit               | Typical |
|------------------------------|--------|--------------------|---------|
| Density, 20 °C               | D 4052 | g/ml               | 0,867   |
| Density, 15 °C               | D 4052 | g/ml               | 0,87    |
| Kinematic Viscosity, 40 °C   | D 445  | mm <sup>2</sup> /s | 35,1    |
| Kinematic Viscosity, 100 °C  | D 445  | mm <sup>2</sup> /s | 7,3     |
| Viscosity Index              | D 2270 | -                  | 178     |
| Brookfield Viscosity, -40 °C | D 2983 | Pa.s               | 32      |
| Pour Point                   | D 97   | °C                 | -45     |
| Flash Point, COC             | D 92   | °C                 | 214     |

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Auto 14 is **1.39** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.  
For more info check here



**we  
take  
care**