

Q8 Corrosion Inhibitor Long Life

Long life corrosion inhibitor

Description

Q8 Corrosion Inhibitor Long Life is an exceptional concentrate that protects the engine against corrosion. If the concentrate is mixed with water it forms a cooling liquid that transfers heat. It contains non-depleting corrosion inhibitors that result in an extremely long coolant lifetime. Q8 Corrosion Inhibitor Long Life is amine-, nitrite-, phosphate-, borate- and silicate-free.

Applications

Q8 Corrosion Inhibitor Long Life is used in cooling systems of heavy duty automotive applications such as construction and off-road equipment as well as stationary internal combustion engines. It is also recommended for the most types of industrial heat transfer and cooling systems. Q8 Corrosion Inhibitor Long Life is Wärtsilä approved for following engine types Wärtsilä 20, 32, 32DF, 34SG, 46, 50DF, 64 and Wärtsilä Vasa 22/26/32,

Benefits

- Outstanding long life protection against all forms of corrosion.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime
- Excellent hard water stability due to the absence of silicates and phosphates.
- Outstanding system metal corrosion protection.
- Environmentally friendly corrosion inhibitor package.

Specifications, recommendations and approvals

| | | | |
|-----------------|-----------------|--------------------|-----------------|
| Caterpillar | MAK | MWM | 0199-99-2091/12 |
| Detroit Diesel | 93K217 | Menag | |
| GEC Alstom | | Navy | BR1326 |
| Holden | | New Sulzer Diesel | TR 1508 - 10/94 |
| Hyundai/Kia | | Newman - Haas | |
| INNIO Jenbacher | TA 1000-0204 | Porsche | |
| Liebherr | MD1-36-130 | Rolls-Royce Bergen | 2.13.01 |
| MAN | B&W A/S | SACM Diesel | DLP799861 |
| MAN | B&W AG D36 5600 | SEMT Pielstick | |
| MB | 312.0 | Waukesha | |
| MIL-Spain | MIL-A-53009 | Wärtsilä | 32-9011 |
| MTU | MTL 5049 | Yanmar | |

Properties

| | Method | Unit | Typical |
|----------------|--------|------|---------------------------|
| Density, 15 °C | D 4052 | g/ml | 1.058 |
| Colour | Visual | - | Colourless to pale yellow |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

7.5-10% Q8 Corrosion Inhibitor Long Life mixed with water is recommended. Best effect is achieved with demineralized water.