SAFETY DATA SHEET

Q8 Formula R Long Life 5W-30



SECTION 1: Identific undertaking	ation of the substance/mixture and of the company/	
1.1 Product identifier		
Product name	: Q8 Formula R Long Life 5W-30	
Viscosity or Type	: SAE 5W-30	
1.2 Relevant identified uses	of the substance or mixture and uses advised against	
Material uses	: Lubricating oil for automotive engines	
1.3 Details of the supplier of	the safety data sheet	
Supplier	: Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Tel. +39 02-90595.1, Fax +39 02-90076347 e-mail: Q8OilsItalia@Q8.it	
Manufacturer / Distributor	: Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Italy / Kuwait Petroleum Belgium N.V./S.A. Petroleumkaai 7 B-2020 Antwerp Belgium	
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communication preferably in English only.	
PCN Information contact	PCNinfo@Q8.com, communication preferably in English only.	
1.4 Emergency telephone nu	ımber	
Italy	: 800 699 792 (Toll free)	
Europe	: +44 (0) 1235 239 670	
Global (English only)	: +44 (0) 1865 407 333	
National advisory body/Po	ison Center	
Italy	: CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA (ROMA) : 06 68593726 Az. Osp. Univ. Foggia (FOGGIA) : 800183459 Az. Osp. "A. Cardarelli" (NAPOLI) : 081-5453333 CAV Policlinico "Umberto I" (ROMA) : 06-49978000 CAV Policlinico "A. Gemelli" (ROMA) : 06-3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica (FIRENZE) : 055-7947819 CAV Centro Nazionale di Informazione Tossicologica (PAVIA) : 0382-24444 Osp. Niguarda Ca' Granda (MILANO) : 02-66101029 Azienda Ospedaliera Papa Giovanni XXII (BERGAMO) : 800883300 Azienda Ospedaliera Integrata Verona (VERONA) : 800011858	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Q8 Formula R Long Life 5W-30

Q8 Formula R Long Life 5W-30				
SECTION 2: Hazards identification				
Ingredients of unknown toxicity	: N	lone.		
Ingredients of unknown ecotoxicity	: N	lone.		
See Section 11 for more det	ailed ir	nformation on health effects and symptoms.		
2.2 Label elements				
Signal word	: N	lo signal word.		
Hazard statements	: N	lo known significant effects or critical hazards.		
Precautionary statements				
General	Р	2103 - Read carefully and follow all instructions. 2102 - Keep out of reach of children. 2101 - If medical advice is needed, have product container or label at hand.		
Prevention	: N	lot applicable.		
Response	: N	lot applicable.		
Storage	: N	lot applicable.		
Disposal	: N	lot applicable.		
Supplemental label elements	: S	Safety data sheet available on request.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: N	lot applicable.		
Detergents - Regulation (EC) No 648/2004	: N	lot applicable.		
Special packaging require	<u>nents</u>			
Containers to be fitted with child-resistant fastenings	: N	lot applicable.		
Tactile warning of dange	: N	lot applicable.		
2.3 Other hazards				
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII		his mixture does not contain any substances that are assessed to be a PBT or a PvB.		
Other hazards which do	: P	Prolonged or repeated contact may dry skin and cause irritation.		

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Severely refined mineral oil (C15 - C50) * - H304	-	≥50 - ≤75	Asp. Tox. 1, H304	-	[1] [2]
Severely refined mineral oil (C15 - C50) * - Not classified.	-	≥25 - ≤50	Not classified.	-	[2]
reaction mass of isomers	REACH #:	≤3	Aquatic Chronic 4,	-	[1]
Date of issue/Date of revision	: 21-08-2023	Date of previous is	ssue : 28-12-2022	Version : 1.0	08 2/

Q8 Formula R Long Life 5W-30

SECTION 3: Composition/information on ingredients of: C7-9-alkyl 3-(3,5-di-tertbutyl-4-hydroxyphenyl) propionate 01-0000015551-76 01-2119878226-29 EC: 406-040-9 CAS: 125643-61-0 H413 See Section 16 for the full text of the H statements declared above. See Section 16 for

* Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25 CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29 CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48 CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms				
Eye contact	: No specific data.			
Inhalation	: No specific data.			

Q8 Formula R Long Life 5W-30

SECTION 4: First aid measures

Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Cussial must satisfy satisfy	. Drevently include the energy hy revealing all nergene from the visibility of the incident if

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

chemical incidents.

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials fo	ontainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Date of issue/Date of revision	: 21-08-2023 Date of previous issue : 28-12-2022 Version : 1.08 4/16

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

- : Not available.
- : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) * -	EU OEL (Europe).
H304	TWA: 5 mg/m³ 8 hours. Form: Mist
	STEL: 10 mg/m ³ 15 minutes. Form: Mist
Severely refined mineral oil (C15 - C50) * - Not	EU OEL (Europe).
classified.	TWA: 5 mg/m³ 8 hours. Form: Mist
	STEL: 10 mg/m ³ 15 minutes. Form: Mist
procedures European Stand assessment of evalues and mea atmospheres - Cof exposure to co (Workplace atmospheres)	Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit isurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 isospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be

SECTION 8: Exposure controls/personal protection

required.

Product/ingredient name	Туре	Exposure	Value	Population	Effects
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl)propionate	DNEL	Long term Dermal	0.006 mg/ cm ²	Workers	Local
	DNEL	Long term Oral	0.16 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.22 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.33 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.74 mg/m ³	General population	Systemic
	DNEL DNEL	Short term Dermal Long term Inhalation	1 mg/cm ² 2.33 mg/m ³	Workers Workers	Local Systemic
	DNEL	Short term Dermal	8.33 mg/ cm²	General population	Local
	DNEL	Short term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	875 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	1750 mg/ m³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

Other skin protection	Appropriate footwear and any additional skin protection measu selected based on the task being performed and the risks invo approved by a specialist before handling this product.	
Respiratory protection	Based on the hazard and potential for exposure, select a respi appropriate standard or certification. Respirators must be use respiratory protection program to ensure proper fitting, training aspects of use. Recommended: Boiling point > 65 °C: A1; Boi AX1; Hot material: A1P2.	d according to a , and other important
Environmental exposure controls	Emissions from ventilation or work process equipment should ensure they comply with the requirements of environmental pro In some cases, fume scrubbers, filters or engineering modificated equipment will be necessary to reduce emissions to acceptable	otection legislation. tions to the process

SECTION 9: Physical and chemical properties

÷

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Oily liquid.]
Appearance	: Clear.
Color	: Brown.
Odor	: Slight
Odor threshold	: Not available.
Melting point/freezing point	: Not applicable.
Pour point	: -42°C (-43.6°F) [ASTM D 97]
Initial boiling point and boiling range	: >300°C (>572°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Flash point	: Open cup: 236°C (456.8°F) [ASTM D 92]
Auto-ignition temperature	: >300°C (>572°F)
Decomposition temperature	: >300°C
рН	: Not applicable.
Viscosity	Kinematic (40°C (104°F)): 67.4 mm²/s (67.4 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 11.8 mm²/s (11.8 cSt) [ASTM D 445]

Solubility(ies)

Media		Result
cold water hot water		Not soluble Not soluble
Partition coefficient: n-octanol/ water	: N	lot applicable.
Vapor pressure	: <	:0.01 kPa (<0.075006 mm Hg)
Density	: 0).85 g/cm³ [15°C (59°F)] [ASTM D 4052]
Vapor density	: N	lot available.
Explosive properties	: N	lot applicable.
Oxidizing properties	: N	lot applicable.
Particle characteristics		
Median particle size	: N	lot applicable.

9.2 Other information

Date of issue/Date of revision

SECTION 9: Physical and chemical properties

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

and Rat - Male, Female Rabbit Rat s and Rat - Male,	5.53 mg/l >5000 mg/kg >5000 mg/kg 5.53 mg/l	4 hours - -
Rabbit Rat	>5000 mg/kg	
Rat	>5000 mg/kg	
and Rat - Male.	5 53 ma/l	
,	0.00 mg/i	4 hours
Female		
Rabbit	>5000 mg/kg	-
Rat	>5000 mg/kg	-
Rat	>2000 mg/kg	-
Rat	>2000 mg/kg	-
	Rabbit Rat Rat	Rabbit >5000 mg/kg Rat >5000 mg/kg Rat >2000 mg/kg

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) * - H304 Severely refined mineral oil (C15 - C50) * - Not classified.	N/A N/A	N/A N/A	N/A N/A	N/A N/A	5.53 5.53

Irritation/Corrosion

Q8 Formula R Long Life 5W-30

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Severely refined mineral oil (C15 - C50) * - H304	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
Severely refined mineral oil (C15 - C50) * - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema Skin - Erythema/Eschar	Rabbit Rabbit	0 0.17	72 hours 72 hours	7 days 7 days

Conclusion/Summary : Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) * - H304	skin	Guinea pig	Not sensitizing
Severely refined mineral oil (C15 - C50) * - Not classified.	skin	Guinea pig	Not sensitizing

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) * - H304	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Severely refined mineral oil (C15 - C50) * - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Conclusion/Summary	: Not available.		

Conclusion/Summary

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative - Dermal - TC	Mouse - Female	-	78 weeks

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Conclusion/Summary	: Not availa	able.		•		

Teratogenicity

Q8 Formula R Long Life 5W-30

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Severely refined mineral oil (C15 - C50) * - H304	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	4	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	:	No specific data.
Delayed and immediate effec	<u>ts</u>	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	1	Not available.
Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	<u>ect</u>	<u>S</u>

Q8 Formula R Long Life 5W-30

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure	
Severely refined mineral oil (C15 - C50) * - H304	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
, , , , , , , , , , , , , , , , , , ,	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week	
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m ³	4 weeks; 5 days per week	
Severely refined mineral oil (C15 - C50) * - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
oldooniou.	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week	
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week	
Conclusion/Summary	: Not available.				
General	: Prolonged or repeated conta or dermatitis.	act can defat the	e skin and lead to irri	itation, cracking and	
Carcinogenicity	: No known significant effects or critical hazards.				

•		5
Mutagenicity	/	: No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
Severely refined mineral oil (C15 - C50) * - H304	Acute NEL >100 mg/l Fresh water	Algae	72 hours	
· · · · ·	Acute NEL >10000 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i>	48 hours	
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days	
Severely refined mineral oil (C15 - C50) * - Not classified.	Acute NEL >100 mg/l Fresh water	Algae	72 hours	
	Acute NEL >10000 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i>	48 hours	
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days	

Conclusion/Summary : Not a

: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) * - H304 Severely refined mineral oil (C15 - C50) * - Not classified.	-	-	Inherent Inherent

12.3 Bioaccumulative potential

Date of issue/Date of revision	Date	of	issu	e/D	ate	of	rev	ision
--------------------------------	------	----	------	-----	-----	----	-----	-------

Q8 Formula R Long Life 5W-30

SECTION 12: Ecological information

J					
Product/ingredient name	LogPow	BCF	Potential		
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl) propionate	9.2	260	Low		

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalo	ogue (EWC)

Waste code	Waste designation			
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils			
Packaging				
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.			
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.			

SECTION 14: Transport information

Q8 Formula R Long Life 5W-30

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

```
14.6 Special precautions for user
```

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substance	<u>es (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)

Q8 Formula R Long Life 5W-30

SECTION 15: Regulatory information

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

<u>Germany</u>		
Hazard class for water (WGK)	:	1
<u>Italy</u>		
D.Lgs. 152/06	1	Not determined.
D.Lgs. 81/2008	1	Health and Safety in the workplace.
D.Lgs. 25/2002	:	Protection against risks from chemical agents.
D.Lgs. 65/2003	1	Classification Labelling and Packaging of Dangerous Products.
D.M. 14/01/2008	:	List of work related deseases that require notification.
Switzerland		
VOC content	:	Exempt.
International regulations		
Chemical Weapon Convention	on	List Schedules I, II & III Chemicals
Not listed.		
Montreal Protocol		
Not listed.		
Stockholm Convention on P	<u>'er</u>	sistent Organic Pollutants
Not listed.		
Rotterdam Convention on P	ric	er Informed Consent (PIC)
Not listed.		
UNECE Aarhus Protocol on	P	OPs and Heavy Metals
Not listed.		
Inventory list		
Inventory list Australia		All components are listed or exempted
		All components are listed or exempted.
Canada		All components are listed or exempted.
China		All components are listed or exempted.
		Russian Federation inventory: Not determined.
Japan	Ċ	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	1	All components are listed or exempted.
Taiwan	1	Not determined.
Thailand	:	Not determined.
Turkey	1	Not determined.
United States of America	:	All components are active or exempted.
Viet Nam	:	Not determined.
15.2 Chemical Safety	:	Chemical Safety Assessments for all substances in this product are either Com

Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

Q8 Formula R Long Life 5W-30

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Indicates information	on that has changed from previously issued version.
Abbreviations and	: ADN = European Provisions concerning the International Carriage of Dangerous
acronyms	Goods by Inland Waterway
-	ADR = The European Agreement concerning the International Carriage of
	Dangerous Goods by Road
	ASTM = American Society for Testing and Materials
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DIN = German Institute for Standardization
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EC = European Commission
	EC50 = Half maximal effective concentration
	EN = European Standard (Norm)
	EUH statement = CLP-specific Hazard statement
	GHS - Globally Harmonized System of Classification and Labeling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IC50 = Half maximal inhibitory concentration
	IMDG = International Maritime Dangerous Goods
	IMO = International Maritime Organisation
	ISO = International Organization for Standardization
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
	NOEL / NOEC = No Observed Effect Level / Concentration
	OECD = Organisation for Economic Co-operation and Development
	OEL = Occupational Exposure Limit
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	Regulation [Regulation (EC) No. 1907/2006]
	RID = The Regulations concerning the International Carriage of Dangerous Goods
	by Rail
	SDS = Safety Data Sheet
	SVHC = Substances of Very High Concern
	STEL = Short Term Exposure Limit
	TLV = Threshold Limit Value
	TWA = Time Weighted Average
	UFI = Unique Formula Identifier
	UN = United Nations
	VOC = Volatile Organic Compound
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

Date of issue/Date of revision

SECTION 16: Other information

	be fatal if swallowed and enters airways. cause long lasting harmful effects to aquatic life.			
Full text of classifications [CLP/GHS]				
Aquatic Chronic 4 Asp. Tox. 1	AQUATIC HAZARD (LONG-TERM) - Category 4 ASPIRATION HAZARD - Category 1			
Training advice	: Ensure operatives are trained to minimise exposures.			
Date of printing	: 21-08-2023			
Date of issue/ Date of revision	of : 21-08-2023			
Date of previous iss	ue : 28-12-2022			
Version	: 1.08			
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands			
Notice to reader				

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.