

Q8 Outboard Synt 4T 10W-40

Synthetic 4-stroke lubricant for outboard engines

Description

Q8 Outboard Synt 4T 10W-40 is an exceptional fully synthetic fluid for outboard engines. Its innovative formulation is based on extremely stable components and a unique anti-wear additive. The universal Q8 Outboard Synt 4T 10W-40 is resistant to mechanical and thermal stress and is highly recommended for outboard engines that demand the highest performance.

Applications

Q8 Outboard Synt 4T is a universal engine oil that is used in several applications such as 4T outboard engines, leisure boats and jetski's. Tested in Bombardier 215 HP SeaDoo.

Benefits

- Best-in-class cylinder protection against scuffing wear.
- Superior protection against rust and corrosion.
- Exceptional cleanliness and wear protection for all components.
- Superior engine wear protection.
- Exceptionally stable fluid viscosity in repeated mechanical stress situations.

Specifications, recommendations and approvals

API	SM	NMMA	TC-W Catalyst Compatible
NMMA	FC-W		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,855
Viscosity Grade	-	-	10W-40
Kinematic Viscosity, 40 °C	ISO 3104	mm ² /s	87
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.2
Viscosity Index	D 2270	-	152
Flash Point, COC	D 92	°C	233
Pour Point	D 97	°C	-36
Total Base Number	D 2896	mg KOH/g	7.6

The figures above are not a specification. They are typical figures obtained within production tolerances.