

Q8 Reynolds OC 150

Schmierfett für extremen Schutz von Freileitungen

Description

Q8 Reynolds OC 150 ist ein äußerst leistungsfähiges anorganisches Schmierfett, das hervorragenden Schutz bietet. Es wurde entwickelt, um Freileitungen vor Korrosion, Oxidation und Reibverschleiß zu schützen. Q8 Reynolds OC 150 garantiert eine verlängerte Lebensdauer, was durch außergewöhnliche Hochtemperatur- und Haftungseigenschaften mit geringem Ausschwitzen von Öl unterstützt wird. Es entspricht in vollem Umfang den strengsten internationalen Standards.

Applications

Q8 Reynolds OC 150 verhindert Korrosion von Freileitungen aus Aluminium, Aluminiumlegierungen, Stahl oder Mehrmetalldrähten. Es wird kalt angewendet und wurde für den Einsatz in äußerst anspruchsvollen Umgebungen entwickelt.

Benefits

- Verlängerte Lebensdauer von Anlagen und somit weniger Ausfallzeiten von Maschinen
- Extremer Schutz vor Korrosion
- Einzigartige Haftfestigkeit
- Extrem hoher Tropfpunkt

Specifications & Approvals

EN

50326:2002 type 40A150

IEC

61394:2011

Properties

	Method	Unit	Typical
Seifenart	-	-	inorganic
Farbe	Visual	-	brown
Konsistenz, Klasse NLGI Nr.	NLGI	-	2 - 2.5
Walkpenetration, 25 °C, 60 Hübe	D 217	0.1 mm	250 - 270
Tropfpunkt	D 566	°C	> 280 (no dropping point)
Oil separation	IP 121	%	0
Temperature range	-	°C	-40° to 150°

The figures above are not a specification. They are typical figures obtained within production tolerances.