

Q8 TO-4 Fluid 10W

Transmission fluid for Caterpillar

Description

Q8 TO-4 Fluid SAE 10W is an outstanding transmission fluid, especially formulated for Caterpillar. This product offers excellent protection at low temperature conditions and facilitates easy starting. It contains additives to prevent oxidation and deposit formation. The oil is suitable for use in equipment where Terra TO-4 fluids are prescribed.

Applications

Q8 TO-4 Fluid SAE 10W is especially formulated for Caterpillar, but also suitable in power shift transmissions, final drives, hydrostatic transmissions, torque converters and hydraulics in heavy duty vehicles. The fluid can be used in off-highway, construction and agricultural equipment.

Benefits

- Superior gear protection under shock load conditions.
- Exceptional wear protection under heavy duty operating conditions.
- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

Allison	C-4	Komatsu	KES 07.868.1
Caterpillar	TO-4	Komatsu Dresser	Micro-Clutch
DANA		Vickers	35VQ25
Eaton/Fuller		ZF	TE-ML 03C

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,880
Density, 15 °C	D 4052	g/ml	0,883
Viscosity Grade	-	-	SAE 10W
Kinematic Viscosity, 40 °C	D 445	mm ² /s	40.1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.3
Viscosity Index	D 2270	-	105
Brookfield Viscosity, -20 °C	D 2983	mPa.s	2850
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	212

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 TO-4 Fluid 10W is **1.29** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**